



OK-A型, OK-B型ストレート軸

軸受 #22200

ユニット番号		主 要 寸 法														取付ボルト		軸 受	
貫通形	軸端形	d	H	A	B	C	E	I	J	K	L	M	N	O	呼び 個数	呼び番	C (kg)	C ₀ (kg)	
OK-210A	OK-210B	50	67	205	60	25	128	45	65	170	-	16	6	23	M14	2	22210	6.450	6.250
OK-211A	OK-211B	55	71	255	70	28	140	48	68	210	-	16	6.5	25	M14	2	22211	9.250	7.950
OK-212A	OK-212B	60	80	255	70	30	155	54	78	210	-	20	8	28	M18	2	22212	11.000	9.650
OK-213A	OK-213B	65	85	275	80	30	165	57	81	230	-	20	8	31	M18	2	22213	13.500	12.200
OK-214A	OK-214B	70	90	280	80	30	175	58	82	230	-	20	8.5	31	M18	2	22214	14.500	13.300
OK-215A	OK-215B	75	90	280	80	30	175	58	84	230	-	20	8.5	31	M18	2	22215	14.500	13.800
OK-216A	OK-216B	80	100	315	90	32	195	64	90	260	-	24	10.5	33	M22	2	22216	16.100	14.900
OK-217A	OK-217B	85	100	315	90	32	195	64	90	260	-	24	9	36	M22	2	22217	19.100	17.800
OK-218A	OK-218B	90	112	345	100	35	224	70	96	290	-	24	10	40	M22	2	22218	22.800	21.900
OK-219A	OK-219B	95	112	345	100	35	224	70	100	290	-	24	8.5	43	M22	2	22219	26.200	25.400
OK-220A	OK-220B	100	125	380	110	40	243	80	110	320	56	22	12	46	M20	4	22220	29.100	28.400
OK-222A	OK-222B	110	132	410	120	45	265	92	122	350	60	22	14.5	53	M20	4	22222	37.500	37.500
OK-224A	OK-224B	120	140	410	120	45	280	92	122	350	60	22	12	58	M20	4	22224	43.500	44.500
OK-226A	OK-226B	130	150	450	130	50	300	96	130	380	65	22	11	64	M20	4	22226	50.000	52.500
OK-228A	OK-228B	140	160	500	150	50	315	106	140	420	80	22	14	68	M20	4	22228	57.500	60.500
OK-230A	OK-230B	150	170	540	160	60	335	115	149	450	92	26	16	73	M24	4	22230	67.500	72.000
OK-232A	OK-232B	160	190	560	170	60	375	125	165	470	92	26	17.5	80	M24	4	22232	81.000	85.500
OK-234A	OK-234B	170	200	660	180	65	412	134	184	560	92	26	19	86	M24	4	22234	88.000	96.500
OK-236A	OK-236B	180	200	660	180	65	412	134	184	560	92	26	19	86	M24	4	22236	90.500	99.500
OK-238A	OK-238B	190	212	680	190	65	425	142	192	580	104	29	20	92	M27	4	22238	101.000	111.000
OK-240A	OK-240B	200	224	740	224	85	450	148	198	610	130	29	20	98	M27	4	22240	115.000	129.000
OK-244A	OK-244B	220	250	820	250	95	500	164	224	680	148	32	23	108	M30	4	22244	141.000	157.000
OK-248A	OK-248B	240	280	880	280	100	560	180	240	740	166	35	25	120	M33	4	22248	154.000	174.000
OK-252A	OK-252B	260	300	940	300	105	600	194	254	790	180	38	27	130	M36	4	22252	176.000	201.000
OK-256A	OK-256B	280	315	990	315	110	630	196	256	830	190	38	28	130	M36	4	22256	183.000	213.000
OK-260A	OK-260B	300	335	1,060	335	115	670	217	277	890	200	41	31	140	M39	4	22260	205.000	237.000

OK-A型, OK-B型ストレート軸

軸受 #23000

ユニット番号		主 要 寸 法														取付ボルト		軸 受	
貫通形	軸端形	d	H	A	B	C	E	I	J	K	L	M	N	O	呼び 個数	呼び番	C (kg)	C ₀ (kg)	
OK-322A	OK-322B	110	112	345	100	35	224	70	104	290	-	24	7.5	45	M22	2	23022	26.000	29.500
OK-324A	OK-324B	120	125	380	110	40	243	80	114	320	56	22	12	46	M20	4	23024	27.900	33.000
OK-326A	OK-326B	130	132	410	120	45	265	92	126	350	60	22	15	52	M20	4	23026	35.500	41.500
OK-328A	OK-328B	140	140	410	120	45	280	92	126	350	60	22	14.5	53	M20	4	23028	37.000	45.000
OK-330A	OK-330B	150	150	450	130	50	300	96	130	380	65	22	15	56	M20	4	23030	41.500	51.000
OK-332A	OK-332B	160	160	470	150	50	315	106	146	390	80	22	18	60	M20	4	23032	48.000	60.000
OK-334A	OK-334B	170	170	540	160	60	335	115	155	450	92	26	19	67	M24	4	23034	56.500	69.000
OK-336A	OK-336B	180	180	560	160	60	355	120	160	470	92	26	18	74	M24	4	23036	66.500	80.500
OK-338A	OK-338B	190	190	560	170	60	375	125	165	470	92	26	20	75	M24	4	23038	68.500	85.500
OK-340A	OK-340B	200	200	660	180	65	412	134	184	560	92	26	21	82	M24	4	23040	71.500	93.500
OK-344A	OK-344B	220	212	680	190	65	425	142	192	580	104	29	21	90	M27	4	23044	83.500	113.000
OK-348A	OK-348B	240	224	740	224	85	450	148	198	610	130	29	23	92	M27	4	23048	87.500	121.000
OK-352A	OK-352B	260	250	820	250	95	500	164	224	680	148	32	25	104	M30	4	23052	111.700	161.000
OK-356A	OK-356B	280	280	880	280	100	560	180	240	740	166	35	32	106	M33	4	23056	122.000	172.000
OK-360A	OK-360B	300	300	940	300	105	600	194	254	790	180	38	33	118	M36	4	23069	145.000	202.000