



OK-AS型, OK-BS型 (スリーブ付)

軸受 #22200

ユニット番号		軸受内径 d	主 要 寸 法													取付ボルト		軸 受			
貫通形	軸端形		H	A	B	C	E	F	G	J	I	K	L	M	N	O	呼び寸数	呼 び 番	C (kg)	C ₀ (kg)	
OK-211AS	OK-211BS	50	71	255	70	28	140	47	47	94	48	210	-	16	6.5	25	M14	2	22211CDK	8.600	7.400
OK-212AS	OK-212BS	55	80	255	70	30	155	47	47	94	54	210	-	20	8	28	M18	2	22212CDK	10.500	9.750
OK-213AS	OK-213BS	60	85	275	80	30	165	50	50	100	57	230	-	20	8	31	M18	2	22213CDK	11.800	11.200
OK-215AS	OK-215BS	65	90	280	80	30	175	50	50	100	58	230	-	20	8.5	31	M18	2	22215CDK	13.700	13.100
OK-216AS	OK-216BS	70	100	315	90	32	195	58	58	116	64	260	-	24	10.5	33	M22	2	22216CDK	14.800	14.600
OK-217AS	OK-217BS	75	100	315	90	32	195	60	60	120	64	260	-	24	9	36	M22	2	22217CDK	18.100	17.900
OK-218AS	OK-218BS	80	112	345	100	35	224	65	65	130	70	290	-	24	10	40	M22	2	22218CDK	20.700	21.000
OK-219AS	OK-219BS	85	112	345	100	35	224	72.5	72.5	145	70	290	-	24	8.5	43	M22	2	22219CDK	24.300	24.900
OK-220AS	OK-220BS	90	125	380	110	40	243	75	75	150	80	320	56	22	12	46	M20	4	22220CDK	27.000	28.200
OK-222AS	OK-222BS	100	132	410	120	45	265	82	82	164	92	350	60	22	14.5	53	M20	4	22222CDK	35.500	37.500
OK-224AS	OK-224BS	110	140	410	120	45	280	82	82	164	92	350	60	22	12	58	M20	4	22224CDK	41.000	44.500
OK-226AS	OK-226BS	115	150	450	130	50	300	87	87	174	96	380	65	22	11	64	M20	4	22226CDK	47.500	53.000
OK-228AS	OK-228BS	125	160	500	150	50	315	96	96	192	106	420	80	22	14	68	M20	4	22228CDK	54.000	61.000
OK-230AS	OK-230BS	135	170	540	160	60	335	105	105	210	115	450	92	26	16	73	M24	4	22230CAK	61.000	68.500
OK-232AS	OK-232BS	140	190	560	170	60	375	112	112	224	125	470	92	26	17.5	80	M24	4	22232CAK	76.000	85.500
OK-234AS	OK-234BS	150	200	660	180	65	412	116	116	232	134	560	92	26	19	86	M24	4	22234CAK	82.500	96.500
OK-236AS	OK-236BS	160	200	660	180	65	412	116	116	232	134	560	92	26	19	86	M24	4	22236CAK	85.000	99.500
OK-238AS	OK-238BS	170	212	680	190	65	425	137	137	274	142	580	104	29	20	92	M27	4	22238CAK	94.500	111.000
OK-240AS	OK-240BS	180	224	740	224	85	450	136	136	272	148	610	130	29	20	98	M27	4	22240CAK	108.000	129.000
OK-244AS	OK-244BS	200	250	820	250	95	500	151	151	302	164	680	148	32	23	108	M30	4	22244CAK	127.000	151.000

OK-AS型, OK-BS型 (スリーブ付)

軸受 #23000

ユニット番号		軸受内径 d	主 要 寸 法													取付ボルト		軸 受			
貫通形	軸端形		H	A	B	C	E	F	G	J	I	K	L	M	N	O	呼び寸数	呼 び 番	C (kg)	C ₀ (kg)	
OK-322AS	OK-322BS	100	112	345	100	35	224	72.5	72.5	145	70	290	-	24		45	M22	2	23022CDK	24.400	29.500
OK-324AS	OK-324BS	110	125	380	110	40	243	82.5	82.5	150	80	320	56	22	12	46	M20	4	23024CDK	26.200	33.000
OK-326AS	OK-326BS	115	132	410	120	45	265	82	82	164	92	350	60	22	15	52	M20	4	23026CDK	33.500	41.500
OK-328AS	OK-328BS	125	140	410	120	45	280	82	82	164	92	350	60	22		53	M20	4	23028CDK	35.000	45.000
OK-330AS	OK-330BS	135	150	450	130	50	300	87	87	174	96	380	65	22	15	56	M20	4	23030CDK	39.000	51.000
OK-332AS	OK-332BS	140	160	470	150	50	315	96	96	192	106	390	80	22	18	60	M20	4	23032CAK	45.000	60.000
OK-334AS	OK-334BS	150	170	540	160	60	335	105	105	210	115	450	92	26	19	67	M24	4	23034CAK	53.000	69.000
OK-336AS	OK-336BS	160	180	560	160	60	355	108.5	108.5	217	120	470	92	26	18	74	M24	4	23036CAK	62.000	80.000
OK-338AS	OK-338BS	170	190	560	170	60	375	112	112	224	125	470	92	26	20	75	M24	4	23038CAK	64.500	85.500
OK-340AS	OK-340BS	180	200	660	180	65	412	116	116	232	134	560	92	26	21	82	M24	4	23040CAK	78.500	107.000
OK-344AS	OK-344BS	200	212	680	190	65	425	137	137	274	142	580	104	29	21	90	M27	4	23044CAK	91.000	125.000