



OK-C型, OK-E型段付軸

軸受 #22200

ユニット番号		主 要 寸 法													取付ボルト		軸 受			
普通形	軸端形	d	H	d ₁	A	B	C	E	I	J	K	L	M	N	O	呼び	個数	呼び番	C (kg)	C ₀ (kg)
OK-210C	OK-210E	50	67	60	205	60	25	128	45	65	170	-	16	6	23	M14	2	22210	6,450	6,250
OK-211C	OK-211E	55	71	65	255	70	28	140	48	68	210	-	16	6.5	25	M14	2	22211	9,250	7,950
OK-212C	OK-212E	60	80	70	255	70	30	155	54	78	210	-	20	8	28	M18	2	22212	11,000	9,650
OK-213C	OK-213E	65	85	75	275	80	30	165	57	81	230	-	20	8	31	M18	2	22213	13,500	12,200
OK-214C	OK-214E	70	90	80	280	80	30	175	58	82	230	-	20	8.5	31	M18	2	22214	14,500	13,300
OK-215C	OK-215E	75	90	85	280	80	30	175	58	84	230	-	20	8.5	31	M18	2	22215	14,500	13,800
OK-216C	OK-216E	80	100	90	315	90	32	195	64	90	260	-	24	10.5	33	M22	2	22216	16,100	14,900
OK-217C	OK-217E	85	100	95	315	90	32	195	64	90	260	-	24	9	36	M22	2	22217	19,100	17,800
OK-218C	OK-218E	90	112	100	345	100	35	224	70	96	290	-	24	10	40	M22	2	22218	22,800	21,900
OK-219C	OK-219E	95	112	110	345	100	35	224	70	100	290	-	24	8.5	43	M22	2	22219	26,200	25,400
OK-220C	OK-220E	100	125	115	380	110	40	243	80	110	320	56	22	12	46	M20	4	22220	29,100	28,400
OK-222C	OK-222E	110	132	125	410	120	45	265	92	122	350	60	22	14.5	53	M20	4	22222	37,500	37,500
OK-224C	OK-224E	120	140	135	410	120	45	280	92	122	350	60	22	12	58	M20	4	22224	43,500	44,500
OK-226C	OK-226E	130	150	150	450	130	50	300	96	130	380	65	22	11	64	M20	4	22226	50,000	52,500
OK-228C	OK-228E	140	160	160	500	150	50	315	106	140	420	80	22	14	68	M20	4	22228	57,500	60,500
OK-230C	OK-230E	150	170	170	540	160	60	335	115	149	450	92	26	16	73	M24	4	22230	67,500	72,000
OK-232C	OK-232E	160	190	180	560	170	60	375	125	165	470	92	26	17.5	80	M24	4	22232	81,000	85,500
OK-234C	OK-234E	170	200	190	660	180	65	412	134	184	560	92	26	19	86	M24	4	22234	88,000	96,500
OK-236C	OK-236E	180	200	200	660	180	65	412	134	184	560	92	26	19	86	M24	4	22236	90,500	99,500
OK-238C	OK-238E	190	212	210	680	190	65	425	142	192	580	104	29	20	92	M27	4	22238	101,000	111,000
OK-240C	OK-240E	200	224	220	740	224	85	450	148	198	610	130	29	20	98	M27	4	22240	115,000	129,000
OK-244C	OK-244E	220	250	240	820	250	95	500	165	224	680	148	32	23	108	M30	4	22244	141,000	157,000
OK-248C	OK-248E	240	280	260	880	280	100	560	180	240	740	166	35	25	120	M33	4	22248	154,000	174,000
OK-252C	OK-252E	260	300	280	940	300	105	600	194	254	790	180	38	27	130	M36	4	22252	176,000	201,000
OK-256C	OK-256E	280	315	300	990	315	110	630	196	256	830	190	38	28	130	M36	4	22256	183,000	213,000
OK-260C	OK-260E	300	335	320	1,060	335	115	670	217	277	890	200	41	31	140	M39	4	22260	205,000	237,000

OK-C型, OK-E型段付軸

軸受 #23000

ユニット番号		主 要 寸 法													取付ボルト		軸 受			
普通形	軸端形	d	H	d ₁	A	B	C	E	I	J	K	L	M	N	O	呼び	個数	呼び番	C (kg)	C ₀ (kg)
OK-322C	OK-322E	110	112	120	345	100	35	224	70	104	290	-	24	7.5	45	M22	2	23022	26,000	29,500
OK-324C	OK-324E	120	125	130	380	110	40	243	80	114	320	56	22	12	46	M20	4	23024	27,900	33,000
OK-326C	OK-326E	130	132	140	410	120	45	265	92	126	350	60	22	15	52	M20	4	23026	35,500	41,500
OK-328C	OK-328E	140	140	150	410	120	45	280	92	126	350	60	22	14.5	53	M20	4	23028	37,000	45,000
OK-330C	OK-330E	150	150	160	450	130	50	300	96	130	380	65	22	15	56	M20	4	23030	41,500	51,000
OK-332C	OK-332E	160	160	170	470	150	50	315	106	146	390	80	22	18	60	M20	4	23032	48,000	60,000
OK-334C	OK-334E	170	170	190	540	160	60	335	115	155	450	92	26	19	67	M24	4	23034	56,500	69,000
OK-336C	OK-336E	180	180	200	560	160	60	355	120	160	470	92	26	18	74	M24	4	23036	66,500	80,500
OK-338C	OK-338E	190	190	210	560	170	60	375	125	165	470	92	26	20	75	M24	4	23038	68,500	85,500
OK-340C	OK-340E	200	200	220	660	180	65	412	134	184	560	92	26	21	82	M24	4	23040	71,500	93,500
OK-344C	OK-344E	220	212	240	680	190	65	425	142	192	580	104	29	21	90	M27	4	23044	83,500	113,000
OK-348C	OK-348E	240	224	260	740	224	85	450	148	198	610	130	29	23	92	M27	4	23048	87,500	121,000
OK-352C	OK-352E	260	250	280	820	250	95	500	164	224	680	148	32	25	104	M30	4	23052	117,000	161,000
OK-356C	OK-356E	280	280	300	880	280	100	560	180	240	740	166	35	32	106	M33	4	23056	122,000	172,000
OK-360C	OK-360E	300	300	320	940	300	105	600	194	254	790	180	38	33	118	M36	4	23060	145,000	202,000