



OKL—C型, OKL—E型段付軸

軸受 #22200

ユニット番号		軸受内径	主 要 寸 法													取付ボルト		軸 受	
貫通形	軸端形	d	H	d ₁	A	B	C	I	J	K	L	M	N	O	呼び	個数	呼び番	C (kg)	C ₀ (kg)
OKL-210C	OKL-210E	50	67	60	164	60	25	45	65	147	-	16	6	23	M14	2	22210	6.450	6.250
OKL-211C	OKL-211E	55	71	65	197	70	28	48	68	175	-	16	6.5	25	M14	2	22211	9.250	7.950
OKL-212C	OKL-212E	60	80	70	203	70	30	54	78	181	-	20	8	28	M18	2	22212	11.000	9.650
OKL-213C	OKL-213E	65	85	75	218	80	30	57	81	196	-	20	8	31	M18	2	22213	13.500	12.200
OKL-214C	OKL-214E	70	90	80	225	80	30	58	82	200	-	20	8.5	31	M18	2	22214	14.500	13.300
OKL-215C	OKL-215E	75	90	85	225	80	30	58	84	200	-	20	8.5	31	M18	2	22215	14.500	13.800
OKL-216C	OKL-216E	80	100	90	253	90	32	64	90	226	-	24	10.5	33	M22	2	22216	16.100	14.900
OKL-217C	OKL-217E	85	100	95	253	90	32	64	90	226	-	24	9	36	M22	2	22217	19.100	17.800
OKL-218C	OKL-218E	90	112	100	285	100	35	70	96	258	-	24	10	40	M22	2	22218	22.800	21.900
OKL-219C	OKL-219E	95	112	110	285	100	35	70	100	258	-	24	8.5	43	M22	2	22219	26.200	25.400
OKL-220C	OKL-220E	100	125	115	308	110	40	80	110	278	56	22	12	46	M20	4	22220	29.100	28.400
OKL-222C	OKL-222E	110	132	125	338	120	45	92	122	308	60	22	14.5	53	M20	4	22222	37.500	37.500
OKL-224C	OKL-224E	120	140	135	345	120	45	92	122	315	60	22	12	58	M20	4	22224	43.500	44.500
OKL-226C	OKL-226E	130	150	150	375	130	50	96	130	340	65	22	11	64	M20	4	22226	50.000	52.500
OKL-228C	OKL-228E	140	160	160	404	150	50	106	140	365	80	22	14	68	M20	4	22228	57.500	60.500
OKL-230C	OKL-230E	150	170	170	435	160	60	115	149	390	92	26	16	73	M24	4	22230	67.500	72.000
OKL-232C	OKL-232E	160	190	180	465	170	60	125	165	420	92	26	17.5	80	M24	4	22232	81.000	85.500
OKL-234C	OKL-234E	170	200	190	542	180	65	134	184	492	92	26	19	86	M24	4	22234	88.000	96.500
OKL-236C	OKL-236E	180	200	200	542	180	65	134	184	492	92	26	19	86	M24	4	22236	90.500	99.500
OKL-238C	OKL-238E	190	212	210	553	190	65	142	192	503	104	29	20	92	M27	4	22238	101.000	111.000
OKL-240C	OKL-240E	200	224	230	596	224	85	148	198	531	130	29	20	98	M27	4	22240	115.000	129.000
OKL-244C	OKL-244E	220	250	250	660	250	95	164	224	590	148	32	23	108	M30	4	22244	141.000	157.000
OKL-248C	OKL-248E	240	280	260	720	280	100	189	240	650	166	35	25	120	M33	4	22248	154.000	174.000
OKL-252C	OKL-252E	260	300	280	770	300	105	194	254	695	180	38	27	130	M36	4	22252	176.000	201.000
OKL-256C	OKL-256E	280	315	300	810	315	110	196	256	730	190	38	28	130	M36	4	22256	183.000	213.000
OKL-260C	OKL-260E	300	335	320	865	335	115	217	277	780	200	41	31	140	M39	4	22260	205.000	237.000

OKL—C型, OKL—E型段付軸

軸受 #23000

ユニット番号		軸受内径	主 要 寸 法													取付ボルト		軸 受	
貫通形	軸端形	d	H	d ₁	A	B	C	I	J	K	L	M	N	O	呼び	個数	呼び番	C (kg)	C ₀ (kg)
OKL-322C	OKL-322E	110	112	120	285	100	35	70	104	258	-	24	7.5	45	M22	2	23022	26.000	29.500
OKL-324C	OKL-324E	120	125	130	308	110	40	80	114	278	56	22	12	46	M20	4	23024	27.900	33.000
OKL-326C	OKL-326E	130	132	140	338	120	45	92	126	308	60	22	15	52	M20	4	23026	35.500	41.500
OKL-328C	OKL-328E	140	140	150	345	120	45	92	126	315	60	22	14.5	53	M20	4	23028	37.000	45.000
OKL-330C	OKL-330E	150	150	160	375	130	50	96	130	340	65	22	15	56	M20	4	23030	41.500	51.000
OKL-332C	OKL-332E	160	160	170	390	150	50	106	146	350	80	22	18	60	M20	4	23032	48.000	60.000
OKL-334C	OKL-334E	170	170	190	435	160	60	115	155	390	92	26	19	67	M24	4	23034	56.500	69.000
OKL-336C	OKL-336E	180	180	200	455	160	60	120	160	410	92	26	18	74	M24	4	23036	66.500	80.500
OKL-338C	OKL-338E	190	190	210	465	170	60	125	165	420	92	26	20	75	M24	4	23038	68.500	85.500
OKL-340C	OKL-340E	200	200	220	542	180	65	134	184	492	92	26	21	82	M24	4	23040	71.500	93.500
OKL-344C	OKL-344E	220	212	240	553	190	65	142	192	503	104	29	21	90	M27	4	23044	83.500	113.000
OKL-348C	OKL-348E	240	224	260	596	224	86	148	198	531	130	29	23	92	M27	4	23048	87.500	121.000
OKL-352C	OKL-352E	260	250	280	660	250	95	164	224	590	148	32	25	104	M30	4	23052	117.000	161.000
OKL-356C	OKL-356E	280	280	300	720	280	100	180	240	650	166	35	32	106	M33	4	23056	122.000	172.000
OKL-360C	OKL-360E	300	300	320	770	300	105	194	254	695	180	38	33	118	M36	4	23060	145.000	202.000